



Advanced Flagpole Products & Services

Phone: 919-304-0009
 Fax: 413-803-4496
 Toll-Free: 877-461-6719

Traditional Flagpole Specification Sheet

Model	Exposed height	Butt diameter	Top diameter	Unflagged Constant Wind Speed	Flagged Constant Wind Speed		Weight
T20	20	4 ^{3/16"}	2 ^{3/4"}	180 ^{MPH}	3 x 5	162 ^{MPH}	22 ^{LBS}
T20-IH	20	4 ^{3/16"}	2 ^{3/4"}	180 ^{MPH}	3 x 5	162 ^{MPH}	22 ^{LBS}
T25	25	4 ^{1/2"}	2 ^{3/4"}	162 ^{MPH}	4 x 6	149 ^{MPH}	33 ^{LBS}
T25-IH	25	4 ^{1/2"}	2 ^{3/4"}	162 ^{MPH}	4 x 6	149 ^{MPH}	33 ^{LBS}
T25-IHL	25	4 ^{1/2"}	2 ^{3/4"}	174 ^{MPH}	4 x 6	162 ^{MPH}	41 ^{LBS}
T30	30	4 ^{14/16"}	2 ^{3/4"}	130 ^{MPH}	5 x 8	112 ^{MPH}	44 ^{LBS}
T30-IH	30	4 ^{14/16"}	2 ^{3/4"}	130 ^{MPH}	5 x 8	112 ^{MPH}	44 ^{LBS}
T30-IHL	30	4 ^{14/16"}	2 ^{3/4"}	162 ^{MPH}	5 x 8	143 ^{MPH}	56 ^{LBS}
T35	35	5 ^{1/4"}	2 ^{3/4"}	118 ^{MPH}	6 x 10	99 ^{MPH}	61 ^{LBS}
T35-IH	35	5 ^{1/4"}	2 ^{3/4"}	118 ^{MPH}	6 x 10	99 ^{MPH}	61 ^{LBS}
T35-IHL	35	5 ^{1/4"}	2 ^{3/4"}	155 ^{MPH}	6 x 10	124 ^{MPH}	76 ^{LBS}
T40	40	5 ^{2/3"}	2 ^{3/4"}	115 ^{MPH}	6 x 10	96 ^{MPH}	80 ^{LBS}
T40-IH	40	5 ^{2/3"}	2 ^{3/4"}	115 ^{MPH}	6 x 10	96 ^{MPH}	80 ^{LBS}
T40-IHL	40	5 ^{2/3"}	2 ^{3/4"}	149 ^{MPH}	6 x 10	121 ^{MPH}	98 ^{LBS}

Note: All flagpoles are available using either a sleeve base or a tilting base.

- «T» stands for Traditional type
- «IH» stands for Internal Halyard / Small access door
- «IHL» stands for Internal Halyard / Large access door